


**Main characteristics**

- > Pink ALBUZ® ceramic orifice (excellent precision and high wear resistance).
- > Flat fan pattern angle 80°.
- > Improves applications near sensitive areas: water courses, field edges... (see graphs below).
- > Designed for all types of nozzle holders, using the same cap as ALBUZ® APE nozzles.
- > All types of treatments (pesticides, insecticides, herbicides, etc)
- > **Recommended pressure: 2 bar.**

OCI


Off center nozzle



**Flow rate chart**

Colour	ISO code	Mesh	(bar)	l/mn	Liters / hectare - nozzle spacing: 50 cm											
					4 km/h	5 km/h	6 km/h	7 km/h	8 km/h	9 km/h	10 km/h	12 km/h	14 km/h	16 km/h	18 km/h	20 km/h
YELLOW	OCI 8002	100	2	0,65	195	156	130	111	98	87	78	65	56	49	43	39
			3	0,80	240	192	160	137	120	107	96	80	69	60	53	48
			4	0,91	273	218	182	156	137	121	109	91	78	68	61	55
BLUE	OCI 8003	50	2	0,98	294	235	196	168	147	131	118	98	84	74	65	59
			3	1,20	360	288	240	206	180	160	144	120	103	90	80	72
			4	1,39	417	334	278	238	209	185	167	139	119	104	93	83
RED	OCI 8004	50	2	1,31	393	314	262	225	197	175	157	131	112	98	87	79
			3	1,60	480	384	320	274	240	213	192	160	137	120	107	96
			4	1,85	555	444	370	317	278	247	222	185	159	139	123	111

**TREATMENT ON BOOM**



**TREATMENT ON PLANTS**

